

www.electrolux.com.mk
www.elektroluks.com.mk
+389 47 203 900
+389 2 329 8 130
made in macedonia

Electrolux



RESTAURANT SUPPLIES INTERNATIONAL



GRIDDLES CREPE MACHINES

Griddles & Crepe Machines

ADVANTAGES

... ENERGY SAVERS
thanks to special cast iron alloy.

... FITS EVERYWHERE
thanks to compact design.

... EASY TO CLEAN
minimum maintenance needed.

... MANY MODELS
for any need.

... OPERATION OF THOUSANDS MODELS
highlights quality



CATERING EQUIPMENT FOR HOTELS, RESTAURANTS, CANTEENS, CAFES • • • • •

1000-L

(10.023.001)

Electric smooth griddle plate with anti-splash surround and drip tray. Constructed of stainless steel, supplied with a 50-300°C, adjustable thermostat, pilot lamp and a thermal fuse with non-automatic return.

Operating voltage: 230 VAC/50Hz
Heating element power: 1800W
Dimensions: 470x375x175mm
Effective surface: 996cm²
Plate dimension: 415x240mm

160 €



1001-LM

(10.023.002)

Electric smooth griddle plate with anti-splash surround and removable drip tray. Constructed of stainless steel, supplied with a 50-300°C, adjustable thermostat, pilot lamp and thermal fuse

Operating voltage: 230 VAC/50Hz
Heating element power: 3200W
Dimensions: 490x490x220mm
Plate dimension: 400x400mm

326 €



1001-L

(10.023.003)

Electric smooth griddle plate with anti-splash surround and removable drip tray (model 1001-L also supplied with storage drawer). Constructed of stainless steel, supplied with a 50-300°C, adjustable thermostat, pilot lamp and thermal fuse.

Operating voltage: 230 VAC/50Hz
Heating element power: 3200W
Dimensions: 460x460x340mm
Plate dimension: 400x400mm

391 €



1002-LR

(10.023.006)

Electric griddle ½ smooth + ½ ribbed plate with anti-splash surround and removable drain drawer. Constructed of stainless steel, supplied with two thermostats 50-300°C, pilot and power lamps and two thermal fuses 210°C.

Operating voltage: 2x(230 VAC/50Hz)
Power consumption: 2x(3000W)
Dimension: 660x460x360mm
Effective surface: 2233cm²
Griddle plate dimension: 620x385mm

529 €



ELECTRIC GRIDDLES

ЕЛЕКТРОЛУКС
Electrolux

450-LR

(10.023.021)

Electric stainless steel griddle plate with smooth surface made of steel. Adjusted by two thermostats. Equipped with large fat collector. Temperature 50-300 °C.

NEW

Operating voltage: 230 VAC/50Hz
Heating element power: 3,2 kw
Dimensions: 460x460x280mm
Cooking surface: 450x450mm

460 €



1002-R

(10.023.004)

Electric ribbed griddle plate with anti-splash surround and removable drain drawer. Constructed of stainless steel, supplied with two thermostats 50-300 °C, pilot and power lamps and two thermal fuses 210 °C.

Operating voltage: 2x(230 VAC/50Hz)
Power consumption: 2x(3000W)
Dimension: 660x460x360mm
Effective surface: 2233cm²
Griddle plate dimension: 620x385mm

518 €



1002-L

(10.023.005)

Electric smooth griddle plate anti-splash surround and removable drain drawer. Constructed of stainless steel, supplied with two thermostats 50-300 °C, pilot and power lamps and two thermal fuses 210 °C.

Operating voltage: 2x(230 VAC/50Hz)
Power consumption: 2x(3000W)
Dimension: 660x460x360mm
Effective surface: 2233cm²
Griddle plate dimension: 620x385mm

513 €



1003-LR

(10.023.007)

Electric griddle plate, high efficiency, with 1/3 ribbed cast iron plate and smooth plate the rest.

Equipped with drip drawer and 2 heated storage drawers.

Stainless steel construction with 2 adjustable thermostats 50-300 °C, pilot lamps and thermal fuse.

Operating voltage: 3x(380 V + N/50Hz)
Power: 3x3000W
Dimensions: 970x535x355mm

1085 €



www.electrolux.com.mk
www.elektroluks.com.mk
+389 47 203 900
+389 2 329 8 130
made in macedonia

1001-LG

(11.123.001)

Gas griddle with smooth cast iron plate, specially designed burner for temperature uniformity. Pilot-burner, adjustable gas flow, piezo-electric lighter. It is equipped with a drip tray.
Safety: Thermocutting devices restraining the passage of gas in case of a damage.



Power: 6500W
Dimension: 460x575x400mm
Plate dimensions: 400x400mm

*Alternative nozzle for every kind of gas are available on request.

400 €

1002-LG

(11.123.003)

Gas griddle with smooth cast iron plate, specially designed burner for temperature uniformity. Pilot-burner, adjustable gas flow, piezo-electric lighter. It is equipped with drip drawer.
Safety: Thermocutting devices restraining the passage of gas in case of a damage.



Power: 7500W
Dimension: 665x575x400mm
Plate dimensions: 590x385mm

*Alternative nozzle for every kind of gas are available on request.

707 €

1002-RG

(11.123.002)

Gas griddle with ribbed cast iron plate, specially designed burner for temperature uniformity. Pilot-burner, adjustable gas flow, piezo-electric lighter. It is equipped with drip drawer.
Safety: Thermocutting devices restraining the passage of gas in case of a damage.



Power: 7500W
Dimension: 665x575x400mm
Plate dimensions: 590x385mm

* Alternative nozzle for every kind of gas are available on request.

702 €

1002-LRG

(10.123.004)

Gas griddle with ½ ribbed + ½ flat cast iron plate, specially designed burner for temperature uniformity. Pilot-burner, adjustable gas flow, piezo-electric lighter. It is equipped with a drip tray. Safety: Thermocutting devices restraining the passage of gas in case of a damage.



Power: 7500W
Dimension: 665x575x400mm
Plate dimensions: 590x385mm

* Alternative nozzle for every kind of gas are available on request.

713 €

LAVASTONES- BARBEQUES

ЕЛЕКТРОЛУКС
Electrolux

PL-1001-LRG

(10.123.007)

Gas burner volcanic stone grill with drip drawer. Specially designed burner for temperature uniformity. Pilot-burner, burner piezo-electric lighter.

Safety: Thermocutting devices restraining the gas supply in case of a malfunction.



Power: 10500W
Dimension: 460x470x400mm

* Alternative nozzle for every kind of gas are available on request.

507 €

PL-1002-LRG

(10.123.008)

Gas burner volcanic stone grill with drip drawer. Specially designed burner for temperature uniformity. Pilot-burner, burner piezo-electric lighter.

Safety: Thermocutting devices restraining the gas supply in case of a malfunction.



Power: 21000W
Dimension: 665x575x400mm

* Alternative nozzle for every kind of gas are available on request.

868 €

BBQ

GARDEN BARBECUE GRILL

gas

Stainless steel construction, easy to handle and easy to storage. The two feet are breakable, therefore it is very ergonomically.

Two wheel helps the user to carry the BBQ to any place he like. Ideal for outdoor catering. Piezo ignition system.



Dimensions: 1250*450*850mm (L*H*D)
Heat input: 6 kW

474 €

www.electrolux.com.mk
www.elektroluks.com.mk
+389 47 203 900
+389 2 329 8 130
made in macedonia

GAS GRIDDLE CADINA

Gas griddle plate with or without burner with stainless steel surface, specially designed burner for temperature uniformity.

Pilot-burner, adjustable gas flow, pressure-electric lighter. It is equipped with a drip tray.

Safety: Thermocutting devices

* Alternative nozzle for every kind of gas are available on request.

CADINA 1

(10.123.012)

Dimensions: 395X500X370mm

Roasting plate: 395x450mm

Power: 5kW

399 €



CADINA 2

(10.123.013)

Dimensions: 570x500x 370mm

Roasting plate: 570x450mm

Power: 10kW

538 €



www.electrolux.com.mk
www.elektroluks.com.mk
 +389 47 203 900
 +389 2 329 8 130
 made in macedonia

NEW LINE GAS GRIDDLES - CADINA

ЕЛЕКТРОЛУКС
Electrolux

CADINA 2K

(10.123.015)

Dimensions: 570x500x 370mm

Roasting plate: 570x 450mm

Power: 10kW



667 €

CADINA 3

(10.123.014)

Dimensions: 570x500x 370mm

Roasting plate: 820x450mm

Power: 15kW



710 €

CADINA 3K

(10.123.016)

Dimensions: 570x500x 370mm

Roasting plate: 820x450mm

Power: 15kW



841 €

www.electrolux.com.mk
www.elektroluks.com.mk
 +389 47 203 900
 +389 2 329 8 130
 made in macedonia

VC35-E (10.028.001).

Single electric crepe machine with 1 plate. Temperature control: one thermostat 50-300 °C.

Operating voltage: 230 VAC/50HZ
Heating element power: 2400W
Plate diameter: 350mm
Dimensions: 372x372x170mm

289 €



VC40-E (10.028.003).

Operating voltage: 230 VAC/50Hz
Heating element power: 2800W
Plate diameter: 400mm
Dimensions: 372x372x170mm

326 €



200 €

NEW ECONOMY LINE

V2C35-E (10.028.002)

Double electric crepe machine with 2 plates. Temperature control: two thermostats 50-300 °C.

506 €

V2C40-E (10.028.004)

Operating voltage: 230 VAC/50Hz
Heating element power: 5600W
Plate diameter: 400mm
Dimensions: 762x372x170mm

580 €



V2C35-E

Operating voltage: 230 VAC/50Hz
Heating element power: 4800W
Plate diameter: 350mm
Dimensions: 762x372x170mm

VC40-G

(11.128.001)

Single gas crepe machine with 1 plate. Control: Thermocutting devices restraining the passage of gas in case of a damage

*Alternative nozzle for every kind of gas are available on request.

Plate diameter: 400mm
Dimensions: 420x510x245mm
Heat input: 6,5kW

343 €



NEW ECONOMY LINE

228 €



V2C40-G

(11.128.002)

Double gas crepe machine with 2 plates.

Control: Thermocutting devices restraining the passage of gas in case of a damage

*Alternative nozzle for every kind of gas are available on request.

Plate diameter: 400mm
Dimensions: 870x510x245mm
Heat input: 13kW

651 €

